

# CERTIFIED SLINGS & Supply

## CROSBY®/BULLARD® GOLDEN GATE® HOOK QUOTATION REQUEST FORM

Customer Name:		Date:
Address:	City:	State, Zip:
Phone:	Fax:	E-Mail:
Person Completing Form:		Quantity:
Sales Order:	P.O.:	
Hoist Name and Model:		Is Self-Closing Gate Required?    Yes    No
Working Load Limit (Tons):	Hook Size:	Top Hook    Bottom Hook

### Shank Length

1. Measure total USABLE shank length from top of hook shank to top of gate assembly. Gate assembly is not considered part of the USABLE shank. When measuring other manufacturer's hooks, measure from the top of the hook shank to the hook shoulder.
2. Measure threaded portion (enter BLANK if threads not required). NOTE: Hook is supplied with Steel Hex-Load Nut and Bronze Load Washer. Hook and Nut threads are National Coarse. If a SPECIAL Load Nut or Load Washer is required, attach a drawing to this form.

### Shank Diameter

3. Measure width of threaded portion.
4. Measure width of blank portion.

### Throat Opening

5. ONLY measure throat opening if this distance is critical to customer's operation.

### Cross Hole in Shank Hooks (complete only if required)

6. Measure shank length from center of hole to top of gate assembly.
7. Measure diameter of hole.

