

CERTIFIED SLINGS *& Supply*

CROSBY® SWIVEL HOIST RING QUOTATION REQUEST FORM

Customer Name:		Date:
Address:	City:	State, Zip:
Phone:	Fax:	E-Mail:
Person Completing Form:		Quantity:
P.O. #:	Certified Slings Representative:	

1. Determine the *Type of Threads* required on the Hoist Ring - Metric or UNC, UNF, Etc. **NOTE - NOT DESIGNED FOR PIPE, ACME OR TAPERED THREADS.**

2. Determine the *Working Load Limit* of the requested Hoist Ring.

3. Determine *Bolt Diameter* - The diameter of the required bolt.

4. Determine *Effective Thread Length* - This is the length the threads must be in order to fully engage, or project through, the work piece. **NOTE: If the Effective Thread Length is not known, the Length of Bolt is required.**

5. Determine *Length of the Bolt* - The over all length of the bolt as measured from under the head of the bolt. **NOTE: If the Effective Thread Length is not known, the Length of the bolt is required.**

6. *# of Thread Threads per Inch (Length Between Threads for Metric threads)* - This information is required to ensure we ship proper bolt size (i.e., 1/2 - 13, 7/8 - 9, 8 x 1.25, etc.).

1. → Thread Type

U.N.C. Thread

Metric Thread

Other

(NOT DESIGNED FOR PIPE, ACME, OR TAPERED THREADS)

2. → Hoist Ring Capacity (Working Load Limit)

_____ lbs. Kgs.

